



Marine & Offshore

Certificate number: 12181/E0 MED

File number: LSA 5338/20

Item number: MED/1.39

This certificate is not valid when presented without the full attached schedule
composed of 7 sections
www.veristar.com

Notified Body 2690 - MARINE EQUIPMENT DIRECTIVE 2014/90/EU

EC TYPE EXAMINATION CERTIFICATE

as per Module B of Directive 2014/90/EU of the European Parliament and of the Council of 23 July 2014 as transposed in the French Regulations and Commission Implementing Regulation (EU) 2022/1157 of 4 July 2022

This certificate is issued to:

SURVITEC GROUP LIMITED
DUNMURRY - UNITED KINGDOM

for the type of product

OPEN REVERSIBLE LIFERAFTS

100 man open reversible inflatable liferaft - HSC pack : ORIL HSCR 100V.

Trademarks: SURVITEC, CREWSAVER, ELLIOT, DSB, SURVITECZODIAC, RFD

Requirements:

SOLAS 74 Convention as amended, Regulations III/4, X/3

IMO Res. MSC.48(66) -(LSA Code)- amended by MSC.207(81), MSC.218(82), MSC.272(85), MSC.293(87), MSC.320(89), MSC.368(93), MSC.425(98), MSC.459(101) and MSC.485(103) I

IMO Res. MSC.36(63) -(1994 HSC Code)- as amended, 8, Annex 10

IMO Res. MSC.97(73) -(2000 HSC Code)- as amended, 8, Annex 11

IMO MSC.1/Circ.1328

This certificate is issued on behalf of the French Maritime Authorities to attest that Bureau Veritas Marine & Offshore did undertake the relevant type-examination procedures for the product identified above which was found to comply with the relevant requirements of the Directive 2014/90/EU of the European Parliament and of the Council of 23 July 2014 as transposed in the French Regulations.

This certificate is a renewal of certificate N° 12181/D0 MED expiring on 27/11/2022

This certificate will expire on: 06 Oct 2027


For Bureau Veritas Marine & Offshore Notified Body 2690,

At BV LONDON, on 06 Oct 2022,

Spencer Yule

This certificate was created electronically and is valid without signature



This certificate does not allow to issue the Declaration of Conformity and to affix the mark of conformity (wheelmark ) to the products corresponding to this type. To this end, the production-control phase module (D, E or F) of Annex II of the Directive is to be complied with and controlled by a written inspection agreement with a notified body.

This certificate remains valid until the date stated above, unless cancelled or revoked, provided the conditions indicated in the subsequent page(s) are complied with and the product remains satisfactory in service. This certificate will not be valid if the applicant makes any changes or modifications to the approved product, which have not been notified to, and agreed in writing with Bureau Veritas Marine & Offshore. Should the specified regulations or standards be amended during the validity of this certificate, the product(s) is/are to be re-approved prior to it/they being placed on board vessels to which the amended regulations or standards apply. Bureau Veritas Marine & Offshore is designated by the French Maritime Authority as a "notified body" under the terms of the French Regulations Division 140 Chapter 140-2. This certificate is issued within the scope of the General Conditions of Bureau Veritas Marine & Offshore available on the internet site www.veristar.com. Any Person not a party to the contract pursuant to which this document is delivered may not assert a claim against Bureau Veritas Marine & Offshore for any liability arising out of errors or omissions which may be contained in said document, or for errors of judgement, fault or negligence committed by personnel of the Society or of its Agents in establishment or issuance of this document, and in connection with any activities for which it may provide.

THE SCHEDULE OF APPROVAL

1. PRODUCT DESCRIPTION:

Trademark	SURVITEC, CREWSAVER, ELLIOT, DSB, SURVITECZODIAC, RFD
Type	ORIL 100V - 100 man Open Reversible Inflatable Liferaft ORIL 100 HSC pack
Weight	220 Kg

Overall dimensions of the inflated liferaft (mm)			Working pressure (mb)
Length	Width	Height	
9300	6100	1000	162

ORIL 151V liferafts may be used as an associated inflatable liferaft of the MES SIS. In such a case, liferafts shall be equipped with either an "end bowing lines arrangement (EBL)" or a "central bowing lines arrangement (CBL)".

As indicated in the technical documentation submitted by the Applicant.

2. DOCUMENTS AND DRAWINGS:

- Drawings and specifications:

Number	Title	Issue	Date
CHXBE 302	SURVITECZODIAC OPEN REVERSIBLE LIFERAFT HSCR 100 V	F	13/09/2022
---	BRANDS FILE	---	29/05/2013

- Material and components:

Number	Title	Issue	Date
D.I.F 02	Suppliers file liferaft COASTAL - TO - TOSR - DL- DLSR - ORIL	W	10/09/2021

- When used in conjunction with a marine evacuation system as an associated liferaft:

Number	Title	Issue	Date
D.I.F 01	Suppliers file MES SIS	K	16/06/2021

- Manual(s) for installation use and maintenance.

No departure from these documents is permitted without the prior consent of the Society.

3. TEST REPORTS:

LIFERAFT TYPE TESTS

Number	Title	Issue	Date
---	Tests performed on the Liferaft	B	13/09/2022

In accordance with requirements contained in the Annex 11 of the IMO Resolution MSC.97(73), open reversible liferafts has been tested in accordance with the recommendations of resolution MSC.81(70), part 1:

- Tests No. 5.5, 5.12, 5.16, 5.17.2, 5.17.10, 5.17.11, 5.17.12, 5.18 and 5.20 have been omitted;
- Part of test No. 5.8 regarding closing arrangement have been omitted,
- The temperature – 30°C in test No. 5.17.3 and 5.17.5 have been substituted with -18°C;

TOWING FORCE

	With the sea anchor deployed	Without the sea anchor deployed
Towed at 2 knots	232 DaN	196 DaN
Towed at 3 knots	420 DaN	315 DaN

TESTS ACCORDING TO THE RECOMMENDATIONS OF THE GUIDELINES MSC.1/CIRC.1328

Number	Title	Issue	Date
---	Tableau récapitulatif des essais EPS (EPS Tests Summary)	---	28/05/2013

4. APPLICATION / LIMITATION:

- As per requirements stated on front page of this certificate.
- Maximum capacity: 100 persons.
- The maintenance of the liferaft shall be carried out according to IMO Resolution A.761(18) as amended and with instructions stated in the Manual(s) for installation use and maintenance.
- Maximum permitted stowage height above waterline : 20 meters

5. PRODUCTION SURVEY REQUIREMENTS:

5.1 - This certificate alone does not allow the applicant to issue the Declaration of Conformity and to affix the mark of conformity (wheelmark) to the products corresponding to this type. To this end, the production-control phase module D Production Quality Assurance or module F Product Verification of Annex II of the Directive is to be complied with and controlled by a written inspection agreement with a Notified Body.

5.2 - The manufacturer shall institute a quality control procedure to ensure that the inflatable liferaft are produced to the same standard as the approved prototype and shall keep records of any production tests carried out in accordance with instructions given in IMO Resolution MSC.81 (70) Part 2.

5.3 - Each liferaft intended to be fitted onboard a ship registered to a National register adhering to the Directive shall be delivered with a Declaration of Conformity.

5.4 - Each equipment, or batch of equipment, is to be supplied with its Manual(s) for Installation, use & maintenance and instructions for servicing stations for frequency and tests to be carried out according to IMO Resolution A.761(18). The servicing stations must be recognized by the manufacturer according to IMO Resolution A.761(18), for their competences to service and repack such life-rafts.

6. MARKING OF PRODUCT:

Markings on container	Markings on inflatable liferaft
Maker's name or trade mark.	
Serial Number	
Name of approving authority	
Reference is made to MED 2014/90/EU chapter 2	
In particular Article 10.3 specifies that the wheelmark shall be followed by the identification number of the Notified Body involved in the production control phase (module D, E or F) and by the year in which the mark is affixed(4 digits or last 2 digits)	
Number of persons it is permitted to carry	Number of persons it is permitted to accommodate over each entrance, in characters not less than 100 mm in height of a colour contrasting with that of the liferaft.
Date when last serviced	Name and place of servicing station where it was last serviced
Type of emergency pack enclosed	Date of manufacture (month and year)
Length of painter	
Maximum permitted stowage height above waterline	
Launching instructions	
NON SOLAS REVERSIBLE	

Provision shall be made for marking each liferaft with the name and port of registry of the ship to which it is to be fitted, in such a form that the ship identification can be changed at any time without opening the container.

In addition, liferafts subject to extended service intervals pursuant to SOLAS regulation III/20.8.3 should be marked to indicate that they have been approved and certified for extended service intervals in accordance with the guidelines MSC.1/Circ.1328.

7. OTHERS:

It is **Survitec's** responsibility to inform shipbuilders or their sub-contractors of the proper methods of fitting, use and general maintenance of the approved equipment and the conditions of this approval.

This certificate supersedes Type Examination Certificate N° 12181/D0 MED, issued on 27/11/2017 by the Society.

This type of liferaft may be subject to **extended service intervals** upon acceptance of the vessel's flag administration pursuant to SOLAS regulation III/20.8.3 and considering that liferafts should be:

- serviced at an approved servicing station at intervals not exceeding 30 months for the first 10 years of their service lives, and thereafter at the frequency required by SOLAS regulation III/20.8.1.1, this being subject to the vessel's Marine Administration acceptance.
- inspected on board by inspection personnel in accordance with the provisions of the MSC.1/Circ.1328 and the instructions of the manufacturer at intervals not exceeding 12 months from the last service or onboard inspection and for the first 10 years of their service life.

*** END OF CERTIFICATE ***